



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21T

SOLENOID VALVE

Series 21T

2-way, direct acting, normally closed solenoid valve

1/8"-1/4"

Pipe Sizes

8W

Coil

0-430 psi

Operating Pressure



Materials Construction

Body:	Brass
Armature Tube:	Brass
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

Electrical Connection

Rating	NEMA 4
Strain Relief Connector	CAGDIN/01
1/2" Conduit Connector	CONDIN/02
6 ft. Power Cord	PCC6FT/03

Note: For more detailed information, please contact us at info@odecanada.com



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21T

SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
FKM	14° – 280°F	Air, Inert Gas, Water, Synthetic oils

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage (AC / DC)
21T1BV17	1/8"	1/16"	0.1	8	0	430	220	12,24,110,220
21T1BV22	1/8"	3/32"	0.14	8	0	290	150	12,24,110,220
21T1BV28	1/8"	1/8"	0.24	8	0	175	85	12,24,110,220
21T1BV40	1/8"	5/32"	0.35	8	0	85	30	12,24,110,220
21T2BV17	1/4"	1/16"	0.1	8	0	430	220	12,24,110,220
21T2BV22	1/4"	3/32"	0.15	8	0	290	150	12,24,110,220
21T2BV28	1/4"	1/8"	0.24	8	0	175	85	12,24,110,220
21T2BV40	1/4"	5/32"	0.35	8	0	85	30	12,24,110,220

Note: For more detailed information, please contact us at info@odecanada.com



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21T

SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
NBR	14° – 195°F	Air, Inert Gas, Water

Model	Pipe Size	Orifice Size	Flow Factor	Watt Rating	Min Pressure	Max Pressure	Max Pressure	Voltage
	(inch)	(Inch)	(CV)	(W)	(PSI)	(AC)	(DC)	(AC / DC)
21T1BB17	1/8"	1/16"	0.1	8	0	430	220	12,24,110,220
21T1BB22	1/8"	3/32"	0.14	8	0	290	150	12,24,110,220
21T1BB28	1/8"	1/8"	0.24	8	0	175	85	12,24,110,220
21T1BB40	1/8"	5/32"	0.35	8	0	85	30	12,24,110,220
21T2BB17	1/4"	1/16"	0.1	8	0	430	220	12,24,110,220
21T2BB22	1/4"	3/32"	0.15	8	0	290	150	12,24,110,220
21T2BB28	1/4"	1/8"	0.24	8	0	175	85	12,24,110,220
21T2BB40	1/4"	5/32"	0.35	8	0	85	30	12,24,110,220

Note: For more detailed information, please contact us at info@odecanada.com